

## LC-203 Dual technology PIR/MW Detector with Pet immunity and Antimasking



### Key Features

- Fully digital PIR
- LODIFF ® optics technology and POLY IR ® materials create a perfect combination of highest quality and efficiency
- Compatible with any hardwired control panel
- Internal EOL resistors built-in
- Double tamper (case / wall) protection
- White light protection and high RFI immunity
- Dual detector (PIR + Microwave)
- Antimasking

The new LC-2xx line of hardwired detectors represents the ultimate choice for residential and industrial security installations.

LC-203 is a fully digital PIR detector. It was designed to deliver unprecedented detection accuracy compared to traditional detectors with analog PIR and digital processing.

Top drawer quality and detection efficiency of LC-203 is achieved thanks to lenses designed using LODIFF ® technology and made from POLY IR ® materials.

In order to shorten the time of installation and simplify the process, the LC-203 features built-in EOL resistors with values required by PowerSeries Neo and PRO control panels. Installers may choose to use their own resistors for compatibility with any other hardwired control panel.

The overall security of the installed system is further enhanced with double tamper protection (case opening and tearing from the wall).

LC-203 is a dual technology detector. It consists of a PIR sensor and a microwave sensor, working in parallel, to reduce number of false alarms, especially in harsh environment. Both sensors need to detect movement in order for alarm to be triggered.

For higher flexibility or special requirements, the detector can trigger an alarm only upon detection from single source (PIR or Microwave). It also has an automatic mode where 5 detections by Microwave sensor in 60 seconds will trigger an alarm regardless of PIR sensor state.

LC-203 is EN Grade 3 certified. This high security grade is achieved thanks to antimasking protection of the detector. The antimasking monitoring is continuous and alert is triggered after 15 seconds of deviation from normal state (power beyond threshold, PIR masking, Microwave masking).

## Specifications

Range	15 meters
Field of view	100 degrees
Lens	Fresnel lens with LODIFF ® technology and POLY IR ®4 materials
LED color	Green (PIR), Yellow (MW), Red (ALARM)
Walk test	Yes
Built in EOL resistors	Yes, 5.6 kOhm
Double tamper (wall / case)	Yes
Creep zone	Yes
Pulse counter	Yes
RFI protection	30 V/m
Temperature compensation	Yes
Mounting	Direct on the wall or with bracket (LC-L2ST)
Power supply	13.8 Vdc
Current draw	27 mA
Pet immunity	Yes, up to 15 kg
Dimensions	114 x 63 x 40 mm
MW Frequency	10.525 GHz

## Approvals

- CE, EN Grade 3

---

## Johnson Controls

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit [www.johnsoncontrols.com](http://www.johnsoncontrols.com) or follow us on Facebook, Twitter, and LinkedIn.