



This remote control is equipped with a Mifare Plus tag. With its 128 bit AES encryption, it makes it unique and prevents from cloning when used with a FDI solution with FDI controllers and readers.

## Technical characteristics



13.56 MHz  
868 MHz

- Dimensions (L X H X D) : 79x38x12mm
- Power supply : flat lithium battery 3 V
- Engraving of a 14 digit alphanumeric number
- Average life of battery : 22000 manipulations
- Coded in factory
- Operating temperature : -20°C to + 60°C
- Use it with the RF receiver FD-020-186 (Wiegand) or FD-020-191 (2SMART for IPassan)

**Disclaimer:** Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.



## Produits associés obligatoires

### Accessoires



FD-020-175  
LECTEUR DE  
PROXIMITE  
CHAMPIGNON  
13.56 MHZ - 2 FILS



FD-020-191  
RECEPTEUR HF  
868MHz 2 FILS



FD-020-208  
LECTEUR DE  
PROXIMITE  
SAILLIE 13.56 MHZ  
- 2 FILS



FD-020-209  
LECTEUR DE  
PROXIMITE P60  
13.56 MHZ - 2 FILS



FD-020-223  
LECTEUR DE  
PROXIMITE P60  
13.56 MHZ - 2 FILS



FD-020-186  
RECEPTEUR HF  
868MHz WIEGAND  
34 BITS

### Gestion à distance en lecture/écriture



GB-150-006  
EASY DOOR  
RECEIVER 868  
MHZ

**Disclaimer:** Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.



[www.fdimatelec.com](http://www.fdimatelec.com)