

Remote Control Switch

RC Remote System Control Locate, Test & Hush

Key Features

- ▶ Allows Remote System Control
- ▶ For use with 'RC' range of hard-wired Alarms
- ▶ Mains powered
- ▶ Locate switch
- ▶ Test switch
- ▶ Hush switch
- ▶ 5 year guarantee



Product Description

The Ei1529RC is a wall mounted triple switch designed for use with the 'RC' range of hard-wired Smoke, Heat and CO alarms.

The Ei1529RC has an alarm Locate switch to allow quick audible identification of the source of alarm. This is particularly useful when a number of Alarms are sounding as the unit sensing the fire or CO can be identified audibly and the premises evacuated or the problems can be quickly resolved.

The Test switch allows the user to test the Alarms easily, without having to access the Alarms on the ceiling.

The third function is the alarm Hush switch. This allows quick and easy silencing of any nuisance alarms from floor level.

The Ei1529RC is supplied complete with its own surface mount pattress and all fixings. It can also be mounted in a standard recessed box (not supplied).

System Wiring

Wiring for Interconnected Alarms with optional Remote System Control Switch & Manual Call Point



Ensure correct wiring of the alarms and switches as mixing Live and Neutral will blow / damage interconnected units.

Technical Specification

Supply Voltage:	230V AC, 50Hz
Mains Check:	The operation of the test switch checks mains power is present.
Temperature:	Operating - 0 to 40°C Storage - 0 to 35°C (in a dry area)
Humidity Range:	0% to 90% Relative Humidity
Button functions:	Test - Test Alarms Locate - Identify triggered alarms Hush - Silence alarms
Interconnect:	Can be connected to a system of up to 12 of the following models: Ei2110 Multi-Sensor - Ei161RC/164RC/166RC/ Ei141RC/144RC/146RC smoke or heat alarms - Ei261ENRC/261DENRC CO alarm - Ei128RBU relay base
Mounting:	Surface mount box supplied. Can also be mounted in standard recessed box (not supplied).
Fixing:	Fixing screws supplied
Dimensions:	89mm x 89mm x 47mm
Weight:	200g
Warranty:	5 year (limited) warranty

Specifications are subject to change